PRINTED: 06/23/2011 DEPARTMENT OF HEALTH AND HUMAN SERVICES FORM APPROVED CENTERS FOR MEDICARE & MEDICAID SERVICES OMB NO. 0938-0391 STATEMENT OF DEFICIENCIES (X1) PROVIDER/SUPPLIER/CLIA (X2) MULTIPLE CONSTRUCTION (X3) DATE SURVEY AND PLAN OF CORRECTION IDENTIFICATION NUMBER: COMPLETED A, BUILDING 01 - MAIN BUILDING 01 B. WING 445359 06/21/2011 NAME OF PROVIDER OR SUPPLIER STREET ADDRESS, CITY, STATE, ZIP CODE 109 HWY 70 NORTH **ROGERSVILLE CARE & REHABILITATION CENTER** ROGERSVILLE, TN 37857 SUMMARY STATEMENT OF DEFICIENCIES (EACH DEFICIENCY MUST BE PRECEDED BY FULL (X4) ID PREFIX PROVIDER'S PLAN OF CORRECTION ID (X5) COMPLETION PREFIX (EACH CORRECTIVE ACTION SHOULD BE REGULATORY OR LSC IDENTIFYING INFORMATION) TAG TAG CROSS-REFERENCED TO THE APPROPRIATE DEFICIENCY) What Corrective action will be accomplished for K 064 NFPA 101 LIFE SAFETY CODE STANDARD K 064 those residents found to have been affected by the SS=F deficient practices? Portable fire extinguishers are provided in all On 6/21/2011 the Maintenance Staff immediately health care occupancies in accordance with adjusted the height of all fire extinguishers in the 9.7.4.1. 19.3.5.6, NFPA 10 facility to lower than 60 inches from the floor to the top How will you identify other residents having the potential to be affected by the same deficient practices and what corrective action will be taken? This STANDARD is not met as evidenced by: On 6/21/2011 the Environmental Service Director Based on observation the facility failed to assure inspected the height of all fire extinguishers and determined that they were all mounted no higher than fire extinguishers were mounted/hung no higher 60 inches from the floor to the top of the handle. than 60 inches from the floor to the tope of the handle. What Measures will be put into place or what systemic changes will you make to ensure the deficient practice does not reoccur? The findings included: On 6/21/2011 the Maintenance Staff were inserviced Observation on June 21, 2011 at 1:00 p.m. by the administrator that all fire extinguishers in the revealed all the fire extinguishers in the facility facility must be mounted no higher than 60 inches from the floor to the top of the handle. were mounted/hung higher than 60 inches. Effective 6/21/2011 the Maintenance Director or Environmental Service Director will measure the height of any new fire extinguisher installation to assure they are mounted no higher than 60 inches from the floor to the top of the handle. How will the corrective action be monitored to ensure the deficient practice will not reoccur, i.c. what quality assurance program will be put into Maintenance Director will report findings to Performance Improvement Committee to include at minimum (Administrator, DON, ADON, Social Service Director) annually,

LABORATORY DIRECTOR'S OR PROVIDER/SUPPLIER REPRESENTATIVE'S SIGNATURE

TITLE

(X6) DATE

Carol Lausn

Administrator

7/2/11

Any deficiency statement ending with an asterisk (*) denotes a deficiency which the institution may be excused from correcting providing it is determined that other safeguards provide sufficient protection to the patients. (See instructions.) Except for nursing homes, the findings stated above are disclosable 90 days following the date of survey whether or not a plan of correction is provided. For nursing homes, the above findings and plans of correction are disclosable 14 days following the date these documents are made evailable to the facility. If deficiencies are cited, an approved plan of correction is requisite to continued program participation.